

2000 Nits Super High Brightness



4K
Native 4K Resolution
HDR
High Dynamic Range
P3
P3 Gamut 99% Coverage
BT.2020
BT.2020 Gamut 90% Coverage
OLED
OLED Panel

65" 4K HDR P3 OLED MONITOR


KXM-6510S, 65inch 4K OLED HDR reference monitor, 3840x2160 resolution with 2x12G-SDI & 2x3G-SDI inputs/outputs. Sub-pixel independent light control, 4,000,000:1 ultra-high contrast ratio and can be used for up to 30,000 hours. Its color gamut can reach more than 99% of DCI-P3 and 90% of BT.2020. Slim body design, fully silent fanless, 0.1ms instantaneous response time is the priority choice for professional and high-quality 4K video live broadcast, shooting, post-production and other applications.

BT.2020
Waveform
VectorScope
Focus Assist
Audio Meter
False Color
Zebra
TSL UMD
GPI

Panel	
Model No.	KXM-6510S
Display Type	OLED, 99% BT.2020
Size	65"
Resolution	3840x 2160
Aspect Ratio	16 : 9
Viewing Angle	178°(H) / 178°(V)
Color Depth	1.07B
Brightness	2000 cd/m ² (Peak Brightness)
Contrast Ratio	4,000,000:1
Input	
1 x SDI SFP+	SDI SFP+ input cage
1 x HDMI 2.0	HDMI 2.0 Signal
2 x BNC	12G-SDI 3/4 signal inputs <small>(Auto-detected and compatible to 6G/3G/HD/SD-SDI)</small>
2 x BNC	3G-SDI 1/2 signal inputs <small>(3G/HD/SD-SDI auto detected)</small>
Output	
2 x BNC	12G-SDI 3/4 signal outputs <small>(Auto-detected and compatible to 6G/3G/HD/SD-SDI)</small>
2 x BNC	3G-SDI 1/2 signal outputs <small>(3G/HD/SD-SDI auto detected)</small>
Audio In & Out	
SDI/HDMI Audio In	16 Channels SDI 2 Channels HDMI embedded audio
Audio Meter Display	Vertical Horizontal audio level meter display
Audio Headset Output	3.5mm headset jack
Built-in Speaker	2.5Wx2
General	
Input Voltage	AC 100-240V 50/60Hz
Power Consumption	500 W
VESA Installation	VESA MIS-D (200x200mm)
Accessory	Power Cord /Desktop stand

▣ Specifications may be changed without prior notice.

Main Body




Specifications

- 3840x2160 4K resolution, 10Bit OLED panel
- Wider Gamut Coverage: 99% DCI-P3, over 90% ITU-R BT.2020
- 12 Bit Video Processing, Anti-Burn-In Technology
- 2 x 12G-SDI inputs and outputs (6G/3G/HD/SD-SDI auto detect)
- 2 x 3G/HD/SD-SDI inputs and outputs
- 4K 12G-SDI single link signal, up to 4096 x 2160 60p
- 4K signal: 2 Sample Interleave (2SI), Square Division (SQD)
- 1 x HDMI 2.0 input, 1 x SDI SFP+ module optical input cage
- 4K Mode, Quad-Split Mode, FHD single picture mode
- 4 x SDI/HDMI Quad-View: mixed inputs & frequency rates
- Free Quad-View (boarder control/window adjustment)
- Payload ID display
- Color Space & EOTF Curves Auto Setting, matching(Rec.709/Rec.2020)
- Color Space (Rec.709/EBU/DCI-P3 D65/DCI-P3/Rec.2020/Bypass)
- HDR: PQ (ST2084), HLG (1.03/1.11/1.16/1.20/1.27/1.33)
- Sony Camera Log Curves: Slog, Slog2, Slog3
- Canon Camera Log Curves: Clog, Clog2, Clog3
- ARRI Camera Log Curves: LogC/DJI Camera Log Curves: Dlog
- Panasonic Camera Log Curves: Vlog, Vlog (softroll)
- DJI Camera Log Curves: D-log
- Gamma (2.0, 2.2, 2.4, 2.6), HDR Area Display
- 4K HDR Waveform, Vector Scope, Marker/Box Control Function
- 3D LUT Color calibration with ColourSpace & CalMAN
- 3rd-party 3D LUT files import(USER1~6)
- S1 - S8 Eight Selectable Scene Settings
- Picture Flip, Focus Assist, False Color, Zebra
- SDR and HDR comparison, Darkness Check
- Full Scan, Over Scan, Blue/Mono Only
- 16ch Embedded Audio Level Meters
- Dynamic and Static UMD Display (TSL3.1/4.0/5.0)
- 608/708 CC Closed Caption
- Key Lock, Video Freeze
- Firmware upgrade/LUT file import via USB/Ethernet
- GPI (selectable/markable windows)
- Aluminum Alloy Casing, Built-in Speaker

4K Signal, Native 4K Resolution


Native 4K resolution, 4K 12G-SDI single link supports utmost 4096 x 2160 60p format, 2 x 12G-SDI signal inputs and outputs (auto detected 6G/3G/HD/SD-SDI), 1xHDMI2.0 input, 1xSDI SFP+ module input cage.



4K(4096x2160) 2K(2048x1080)


Unparalleled black level

Featuring a 1,000,000:1 contrast ratio with an absolute black of 0.0005 nit, OLED panel reproduces extreme black details, and brings a stunning experience.



EOTF Curve Conversions

Konvison KUM 4K, 8K and KVM-6X series supports a variety of EOTF curve conversion applicable to the broadcast industry and digital film standard. A preset of lots of camera logs and gamma curve selections, so as to realize the perfect combination with the camera system.




HDR Waveform, HDR Area Display

HDR reference white is 203nits. The part that exceeds the reference white level (203nits) considered as the HDR highlight part, and the HDR highlight ratio should not exceed 20% of the entire image. HDR waveform, HDR area display can make the HDR info more intuitively displayed, which is more convenient for users.



2SI and SQD 4K signal



4K 2 Sample Interleave (2SI) : Pixel based segmentation



4K Square Division (SQD) : Quadrant based segmentation

Fastest Response Time

The OLED panels' response time is only 0.1ms! Far exceeding the normal LCD, perfectly bids farewell to the phenomenon of trailing and jaggies of high-speed moving pictures. This rapid fast response benefits to the smooth fast-moving content, great for sports broadcasting.



LCD

OLED

TC:06:36:26:10

TC:06:36:26:14

Next frame

Anti-Burn-In Technology

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame

Next frame